

|                         |  |
|-------------------------|--|
| <b>Model Name</b>       | <b>F170MN/MP</b>   |
| <b>Description</b>      |  |
| <b>Product Features</b> | <p>17" Open Frame design Monitor</p> <p>17" diagonal screen with native resolution 1280*1024</p> <p>4:3 Aspect ratio</p> <p>Low power consumption only 20W</p> <p>Design perfectly for kiosk, equipment and instrument instalation</p> <p>VESA 75 x 75 wall mounting standard</p> <p>10-Point Projected Capacitive Touch Panel, multi touch technology (F170MP)</p> <p>User friendly OSD control buttons w/key lockable</p>  |
| <b>Specification</b>    | <p>MN= Non-touch design, MP= Projected capacitive touch screen</p> <p>Panel resolution<br/>1280 * 1024</p> <p>Active display area<br/>337.920mm (H) × 270.336mm(V)</p> <p>Brightness / Contrast<br/>250cd/m2 / 1000:1</p> <p>Viewing Angles<br/>Horiz: 85/85, Vert.: 80/80</p> <p>Backlight<br/>LED, Life time 30K hours</p> <p>Power<br/>External power adapter, AC IN: 100 ~ 240V ; DC OUT: 12V / 3.0A</p> <p>Power Consumption<br/>Max. 20W</p> <p>Suppot Resolution<br/>1280*1024, 1024*768, 800*600, 640*480, 720*400</p> <p>I/O<br/>Video in:VGA, DVI-D, HDMI, USB port for touch Model (F170MP): USB B type</p> <p>Touch panel<br/>10-Point Projected Capacitive Touch Panel, USB control</p> <p>Temperature(Operaton/Storage)<br/>0°C to 40°C / -20°C to 60°C</p> <p>Humidity<br/>20% to 90% non-condensing</p> <p>Weight<br/>TBD</p> <p>Physical Dimensions<br/>418.5mm x 356.5mm x 47.1mm</p> <p>Accessory<br/>VGA cable, , USB cable (F170MP), CD, Optional: HDMI cable</p> |

### Product Image



### Product Mechanical Dimensions

