



\*White Color support by request

## Large size

Poindus big size displays offer robust solution for your business needs with touch screen convenience. With the number of different accessories offered such as MSR, fingerprint reader, iButton, smart card reader and customer display, no matter retail, hospitality or automation applications can be fully supported as your needs. We offer the most commonly accepted VGA and DVI-D interface with locking for secure connection. All our displays been designed with cable management in mind either with desk stand or VESA mounting option to reduce cable clutter and have more esthetic look neatly securing the cables out of the way. If our standard models not suiting your need, do let us know for customized solution. Our modular design allows us to make changes to suit your needs as well as our open frame solutions custom build to your specifications can fulfill your unique applications from Kiosk to digital signage installations.



	M337	M437	M367	M467	M458	M168
Display Size	15"	15"	15"	15"	17"	18.5"
Ratio	4:3	4:3	4:3	4:3	4:3	16:9
Touch Type	Resistive PCAP	Available N/A	Available N/A	Available(ELO) Available	Available(ELO) Available	(Project) Available Available
Ingress Protection	-	-	IP54 (Front)	IP54 (Front)	IP54 (Front)	IP54 (Front)
Resolution	1024 x 768	1024 x 768	1024 x 768	1024 x 768	1280 x 1024	1366 x 768 / 1920 x 1080
Brightness (nits)	250	250	250	250	250	250
Viewing Angle	70/70/80/80 degree	70/70/80/80 degree	70/70/80/80 degree	70/70/80/80 degree	80/80/85/85 degree	80/80/85/85 degree
Contrast Ratio	700 : 1	700 : 1	700 : 1	700 : 1	1000 : 1	1000 : 1
Response Time (ms)	16	16	16	16	5	5
<b>Interface</b>						
Video Signal	VGA, DVI-D	VGA, DVI-D	VGA, DVI-D	VGA, DVI-D	VGA, DVI-D	VGA, DVI-D
Power	12V DC Jack	12V DC Jack	12V DC Jack	12V DC Jack	12V DC Jack	12V DC Jack
<b>Physical Dimension</b>						
Dimensions (W x H x D) mm	365.7 x 323.5 x 51	365.7 x 323.5 x 199.7	361.6 x 278.6 x 47.1	361.6 x 339.3 x 220	399.2 x 381.5 x 200	472 x 293 x 43
Weight (N. W.) (Kg)	3.5	4.6	3.3	4.7	5.86	5.86
<b>Environment</b>						
Operating Condition	0°C~40°C	0°C~40°C	0°C~40°C	0°C~40°C	0°C~40°C	0°C~40°C
Storage Condition	-10°C~50°C	-10°C~50°C	-10°C~50°C	-10°C~50°C	-10°C~50°C	-20°C~60°C
Power Consumption	Max. 20W	Max. 20W	Max. 20W	Max. 20W	Max. 20W	Max. 30W
<b>Certifications</b>						
EMI / Safety	CE, FCC, LVD	CE, FCC, LVD	CE, FCC, LVD	CE, FCC, LVD	CE, FCC, LVD	CE, FCC, LVD
<b>Options</b>						
VESA Support	75*75	75*75	75*75	75*75	100*100	75*75
Base	M437	Plastic Base	M467	Die-Cast Aluminum Base	Plastic Base	Optional