

PM2655-2F30L0

Specification

Panel Mount, 26.5" LCD monitor, 1920 x 1920, LED 300 nits, 1 x VGA + 5 x HDMI + 1x DP



Features

- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Available with auto-brightness sensor offers application in day and night
- VGA connector with optional AV,SV,AV-Looping
- Complete custom design/solution for OEM customers

| | | | |
|---------------------|--|---|---|
| Panel | Cell Type / Glass Surface | TFT LCD / Black Anti-Glare, low reflection coating | |
| | Aspect Ratio / Size | 1 : 1 / 26.5" viewable diagonal area | |
| | Active Area / Pixel Pitch | 491.8(H) x 491.8(V) mm / 0.2478(H) x 0.2478(V) mm | |
| | Native Resolution / Colors | 1920(H) x 1920(V) / 16.7 M | |
| | Brightness / Contrast | 300 cd/m ² (typ) / 1000 : 1 | |
| | Response Time | ≤ 28ms | |
| | Viewing Angle (typical) | H. 178° (- 89° ~ + 89°) , V. 178°(- 89° ~ + 89°) | |
| | Light Source | LED backlight, Long life, 35,000 hrs (typ) | |
| Input Sources | PC System | Signal | Analog RGB (0.7/1.0 V _{p-p} , 75 ohms) |
| | | Sync | Separate Sync, Composite Sync, Sync On Green |
| | | Frequency | F _h : 30 - 82Khz , F _v : 50 -75Hz |
| | Audio System | 2W speaker x 2 | |
| Input Terminals | 1 x VGA + 5 x HDMI + 1x DP, 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug | | |
| Convenient Features | Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B) | | |
| | OSD Multi-Languages , Wall Mount Ready (VESA Dimension - please refer to Drawing) | | |
| Power | Internal power supply with universal / Auto-Sensing, AC90 to 260V, 50/60 Hz | | |
| Power Consumption | Operation / Power Saving | 117.5 watt , < 5 watt (Support DPMS) | |
| Operating Condition | Temperature / Humidity | 0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation) | |
| Storage Condition | Temperature / Humidity | - 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation) | |
| Certification | FCC , CE | | |
| Dimensions | Physical | Please refer to Drawing | |
| | Carton | W x H x D = TBD | |
| Weight | N.W. / G.W. | 12 Kgs / 13.5 Kgs | |
| Container Loaded | 20ft / 40ft / 40ft HQ | TBD (Sets , By pallet) | |

| | | |
|---------|--------------------------|------------------------------|
| Options | Enhanced Panel | Others |
| | Panel with LED backlight | Digital Signage(Stand alone) |
| | High brightness panel | Networking Digital Signage |
| | Wide Temperature | Motion Sensor |
| | Sunlight Readable | Light Sensor |
| | | Auto-Dimming |