

## Professional Series



Green  
Power



Environmental  
Friendly



Energy  
Saving



## PowerCube 800U

Line Interactive UPS

- User Friendly LED Indicator
- 4 x Universal Socket Output with Safety Window
- Boost & Buck AVR
- High Quality Sealed Lead Acid Maintenance Free Battery  
- CSB/LEOCH/YUASA Japan Battery
- Hot-Swappable Battery Design
- Built-in EMI/RFI Noise Filter
- Lightning, Spike & Surge Protection
- Modem/Fax/Network Line Protection (RJ 45) \*Optional
- Comes with RS-232 Port, USB Port & Power Management Software \*Optional



• Boost &  
Buck AVR



• 3 Years •  
Warranty

# Professional Series



Green Power



Environmental Friendly



Energy Saving

# RIGHT POWER

The Power Of Continuity



Technical Specification:

MODEL	PowerCube 800U
CAPACITY (VA)	800VA
<b>INPUT</b>	
INPUT VOLTAGE	220V / 230V / 240V
VOLTAGE RANGE	140-290VAC
INPUT FREQUENCY	50/60Hz (Auto-Sensing)
<b>OUTPUT</b>	
VOLTAGE RANGE	220V+/-5% with Built In Automatic Voltage Regulator (AVR) for Voltage Adjustment
OUTPUT FREQUENCY	50 Hz or 60 Hz +/-1Hz
WAVEFORM	Simulated Sinewave
TRANSFER TIME (Typical)	2ms - 6ms
OUTPUT SOCKET	4 x Universal Sockets c/w Safety Window
<b>BATTERY</b>	
SEALED LEAD ACID MAINTENANCE FREE - CSB / LEOCH / YUASA Japan Battery	12V 7Ah x 1pc
HOT-SWAPPABLE BATTERY (USER REPLACEABLE DESIGN)	Yes ( Able to replace battery without turning off UPS)
BACK UP TIME (Depending on Load)	5 - 30 minutes
RECHARGING TIME	4 - 6 Hours to 90% After Complete Discharge
BATTERY PROTECTION	Automatic Detection and Discharge Protection
<b>STATUS INDICATOR</b>	
LEDs: POWER INDICATION	AC Mode, Battery Mode, Fault, Overload
AUDIBLE ALARMS	Backup Mode, Low Battery, Battery Replacement, Overload, UPS Fault
<b>COMMUNICATION</b>	
POWER MANAGEMENT SOFTWARE (OPTIONAL)	Support Window Family, Linux & MAC
	- Automatically Shut-down, Saves Application Data Before Exit
	- Schedules System Shutdown/Restart
	- Remote Monitor/Control via LAN
	- Records Logs for Analysis
INTERFACE (OPTIONAL)	RS232 & USB Port
<b>SURGE PROTECTION &amp; FILTERING</b>	
EMI/RFI NOISE FILTER	Meet EN50081 - 1 or FCC Part 15 Class A & B
LIGHTNING PROTECTION	Yes
SURGE PROTECTION	Yes
OVERLOAD PROTECTION	Fuse, Current Limited & Cut-off (Re-settable Circuit Breaker)
PHONE / FAX / MODEM / NETWORK PROTECTION (OPTIONAL)	RJ 45 (1 in 1 out)
<b>PHYSICAL</b>	
OPERATING ENVIRONMENT	0-40°C, 0-90% Relative Humidity (Non-Condensing)
NOISE LEVEL	Less Than 40dB
DIMENSION (D x W x H) mm	292 x 199 x 91
WEIGHT (KG)	5.8
<b>WARRANTY</b>	
UPS WARRANTY	3 Years Full Warranty Include Parts & Labour. 2 Years for Battery

\*Specification subjects to change without prior notice

