

L1588-XN25L0

Specification



Features

- Foldable stand adds flexibility and comfort to your viewing preferences
- Input sources switch by hot key
- Designed for global application, auto detect NTSC, PAL and SECAM video system
- Option : Looping function(AV2, AV2-Looping)



Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating		
	Aspect Ratio / Size	4 : 3 / 15" viewable diagonal area		
	Active Area / Pixel Pitch	304.13(H) x 228.10(V) mm / 0.297(H) x 0.297(V) mm		
	Native Resolution / Colors	1024(H) x 768(V) / 16.2 Million		
	Brightness / Contrast	250 cd/m ² (typ) / 700 : 1		
	Response Time	≤ 35 ms		
	Viewing Angle (typical)	H. 140° (- 70° ~ + 70°) , V. 120°(- 60° ~ + 60°)		
	Light Source	LED , Long life, 35,000 hrs (typ)		
Input Sources	Video System	NTSC / PAL / SECAM supported (Auto detecting)		
	PC System	Signal	Analog RGB (0.7/1.0 V _{p-p} , 75 ohms)	
		Sync	Separate Sync, Composite Sync, Sync On Green	
		Frequency	F _h : 30 - 82Khz , F _v : 50 - 75Hz	
Audio System	2W speaker x 2			
Input Terminals	1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug			
	1 x S-Video , 1 x CVBS(BNC) , 2 x Audio(RCA, Audio-R + Audio-L)			
Convenient Features	Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)			
	OSD Multi-Languages , Wall Mount Ready (VESA 75 x 75 mm)			
Power	External AC-to-12VDC power adapter with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz			
Power Consumption	Operation / Power Saving	20 watt , < 2 watt (Support DPMS)		
Operating Condition	Temperature / Humidity	0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)		
Storage Condition	Temperature / Humidity	- 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation)		
Certification		FCC , CE		
Dimensions	Physical	With Base(W x H x D) : 356.9 x 340.8 x 185.0 mm		
		Without Base(W x H x D) : 419 x 380 x 142 mm		
	Carton	W x H x D = 419 x 380 x 142 mm		
Weight	N.W. / G.W.	4.0 Kgs / 5.0 Kgs		
Container Loaded	20ft / 40ft / 40ft HQ	TBD (Sets , By pallet)		

Options	Video / TV	Enhanced Panel
	AV2	Panel with LED backlight
	AV2-Looping	High brightness panel
		Wide Temperature
		Sun Light Readable

Winsonic[®]

Winsonic Electronics CO.,LTD. TEL:886-3-3704789 FAX:886-3-3704722 E-mail:sales@ewinsonic.com
No.290-1 Wun-Jhong Rd. Taoyuan City, Taoyuan Taiwan R.O.C

Online Download

www.ewinsonic.com