

Model Name	F190MN/MP
Description	
<b>Product Features</b>	19" Open Frame design Monitor 19" diagonal screen with native resolution 1280*1024 4:3 Aspect ratio Low power consumption only 20W Design perfectly for kiosk, equipment and instrument instalation VESA 75 x 75, or 100x100 wall mounting standard 10-Point Projected Capacitive Touch Panel, multi touch technology (F190MP) User friendly OSD control buttons w/key lockable
<b>Specification</b>	MN= Non-touch design, MP= Projected capactive touch screen Panel resolution 1280 * 1024 Active display area 376.32mm (H) x 301.06mm (V) Brightness / Contrast 250cd/m2 / 1000:1 Viewing Angles Horiz: 85/85, Vert.: 80/80 Backlight LED, Life time 30K hours Power External power adapter, AC IN: 100 ~ 240V ; DC OUT: 12V / 3.0A Power Consumption Max. 20W Suppot Resolution 1280*1024, 1024*768, 800*600, 640*480, 720*400 I/O Video in:VGA, DVI-D, HDMI, USB port for touch Model(F190MP): USB B type Touch panel 10-Point Projected Capacitive Touch Panel, USB control Temperature(Operation/Storage) 0°C to 40°C / -20°C to 60°C Humidity 20% to 90% non-condensing Weight TBD Physical Dimensions 458mm x 384mm x 47.1mm Accessory VGA cable, , USB cable (F190MP), CD, Optional: HDMI cable

### Product Image



### Product Mechanical Dimensions

